

Principal dimensions			Basic load ratings		Pu	Speed ratings		Weight kg	Designation	Dimensions						Abutment and fillet dimensions						Value	
(mm)			KN			rpm				mm						mm							
d	D	B	dyc Cr	stc Cor		Speed Ratings	Limiting Speed			d	d ₁ ~	F	r _{1,2} Min	r _{5,4} Min	s ⁽¹⁾	d ₁ Min	d ₂ Max	d ₆ Min	D ₁ Min	D ₂ Max	r ₆ Max		r ₅ Max
85	180	41	340	335	11,5	4000	4800	5,25	*NU317ECM/C3VL0241	85	153	108	3	3	2,3	99	105	111	158	166	2,5	2,5	0,15
90	160	30	308	290	27	4500	5000	2,75	*NU318ECM/C3VL0241	90	139	107	2	2	1,8	101	104	110	144	149	2	2	0,15
95	300	45	390	390	46,5	3600	4300	7,25	*NU319ECM/C3VL0241	95	170	121,5	3	3	2,9	109	118	124	175	186	2,5	2,5	0,15
110	240	50	530	540	61	3000	3400	12,0	*NU322ECM/C3VL0241	110	201	143	3	3	3	124	139	146	207	226	2,5	2,5	0,15
120	260	55	610	620	69,5	2800	3200	15,2	*NU324ECM/C3VL0241	120	219	154	3	3	3,7	134	150	157	226	246	2,5	2,5	0,15